

This procedure presents the minimum requirements to sanitize and empty the water tank of your machine. Follow these steps to get your unit back up and running after a water cutting or a boil water advisory.

To perform this procedure, water valve must be OFF.

Before turning water valve off or back on, ask your coffee supplier's permission.

DURING A BOIL WATER ADVISORY

- 1 Turn the unit off and disconnect it from the fresh water line.
Wait at least 30 minutes to allow water in the tank to cool down.
- 2 Drain the water tank.
- 3 Connect the unit to a bottled water system (we recommend using the *5000 Series Flojet pump*).
- 4 Clean and sanitize all parts in contact with water in accordance with the manufacturer's instructions.

Water tank
 Brew group

Valves
 Water Hoses

Spout Assembly
 Drip Tray

NOTE: You will need clean drinking water in order to sanitize your machine. If you do not have a bottled water system available, you will need to perform the cleaning after the water filter replacement.

- 5 Keep the bottled water system in place as long as the boil water advisory is in effect.



The unit is now ready to serve coffee again!



AFTER THE BOIL WATER ADVISORY

- 7 Disconnect the in-line water filter from the fresh water input.
- 8 Flush the fresh water line.
- 9 Following the manufacturer's instructions, install a new filter.
- 10 Reconnect the coffee machine to the fresh water line.
- 11 Refill the unit water tank.

NOTE: If you did not use a bottled water system, perform the cleaning and sanitizing procedure in accordance with the manufacturer's instructions as indicated at Step 4.